UL Product iQ®



Model 93020LE

File Number: MH17478

COMPANY

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV 3M CENTER BLDG 230-3G-07 SAINT PAUL, MN 55144-1001 United States

MODEL INFO

93020LE

Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Acrylonitrile butadiene styrene		-35	75	Yes	Yes	
Fluorinated ethylene propylene (flexible)		-35	75	Yes	Yes	
Glass		-35	75	Yes	Yes	
Polycarbonate		-35	75	Yes	Yes	
Polyester		-35	75	Yes	Yes	
Co-Polyester		-35	65	Yes	Yes	
Polycarbonate/Siloxane		-35	65	Yes	Yes	Yes
Polymethyl methacrylate		-35	65	Yes	Yes	





The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."