

iq.ul.com

Marking and Labeling System Materials

MH26206

Guide Information

**3M COMPANY**

INDUSTRIAL ADHESIVES & TAPES DIV, 3M CENTER, BLDG 230-3G-07, SAINT PAUL MN 55144-1001

**7945MP, 7953MP, 7953MPP, 7956MP, 7956MWS, 7956WDL, 7957MP, 7959MP, 7961MP, 7966MWS, 7966WDL, 9045MP, 9056MP, 9057MP, 9057MPW, 9059MP, 9061MP, 9495B, 9495BF, 9495MP, 9495MPF, 92015, 7945MPL, 7953MPL, 7956MPL, 7957MPL, 7959MPL, 7961MP**

Pressure-sensitive laminating adhesives "3M® Laminating Adhesive"

<u>Face Stock</u>	<u>Face Stock</u> <u>Thk mm</u>	<u>Application Surface</u>	<u>Max Temp</u> <u>(°C)</u>	<u>Min Temp</u> <u>(°C)</u>	<u>Indoor</u> <u>Use</u>	<u>Outdoor</u> <u>Use</u>	<u>Additional</u> <u>Conditions</u>
Aluminum	0.051 - 0.813	Aluminum	150	-40	Yes	Yes	-
	0.051 - 0.813	Galvanized steel	150	-40	Yes	Yes	-
	0.051 - 0.813	Porcelain	150	-40	Yes	Yes	-
	0.051 - 0.813	Stainless steel	150	-40	Yes	Yes	-
	0.051 - 0.813	Alkyd paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.051 - 0.813	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.051 - 0.813	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
Polycarbonate	0.127 - 0.508	Epoxy	100	-40	Yes	Yes	-
	0.127 - 0.508	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.127 - 0.508	Alkyd paint	80	-40	Yes	Yes	-
	0.127 - 0.508	Aluminum	80	-40	Yes	Yes	-
	0.127 - 0.508	Galvanized steel	80	-40	Yes	Yes	-
	0.127 - 0.508	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.127 - 0.508	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
	0.127 - 0.508	Polycarbonate	60	-40	Yes	Yes	-
	0.127 - 0.508	Polyurethane paint	60	-40	Yes	Yes	-
	0.127 - 0.508	Porcelain	60	-40	Yes	Yes	-
	0.127 - 0.508	Stainless steel	60	-40	Yes	No	-
	0.127 - 0.508	Polyethylene terephthalate	40	-40	Yes	Yes	-
Polyester	0.076 - 0.178	Epoxy	100	-40	Yes	Yes	-
	0.076 - 0.178	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.076 - 0.178	Alkyd paint	80	-40	Yes	Yes	-
	0.076 - 0.178	Aluminum	80	-40	Yes	Yes	-
	0.076 - 0.178	Galvanized steel	80	-40	Yes	Yes	-
	0.076 - 0.178	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyethylene terephthalate	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyurethane paint	60	-40	Yes	Yes	-
	0.076 - 0.178	Porcelain	60	-40	Yes	Yes	-
	0.076 - 0.178	Stainless steel	60	-40	Yes	No	-
	0.076 - 0.178	Polycarbonate	40	-40	Yes	Yes	-

<u>Canadian Application</u> <u>Face Stock</u>	<u>Face Stock</u> <u>Thk mm(in)</u>	<u>Canadian Application Surface</u>	<u>Max Temp</u> <u>(°C)</u>	<u>Indoor</u> <u>Use</u>	<u>Outdoor</u> <u>Use</u>	<u>Additional</u> <u>Conditions</u>
Aluminum	0.051 - 0.813	Metals	150	Yes	Yes	-
	0.051 - 0.813	Porcelain	150	Yes	Yes	-
	0.051 - 0.813	Plastic Group II	80	Yes	Yes	-
	0.051 - 0.813	Plastic Group V	80	Yes	Yes	-
	0.051 - 0.813	Plastic Group VI	80	Yes	Yes	-
Polycarbonate	0.127 - 0.508	Metals	100	Yes	Yes	-
	0.127 - 0.508	Plastic Group VIII	100	Yes	Yes	-
	0.127 - 0.508	Plastic Group II	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group V	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group VI	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group III	60	Yes	Yes	-
Polyester	0.076 - 0.178	Metals	100	Yes	Yes	-
	0.076 - 0.178	Plastic Group VIII	100	Yes	Yes	-
	0.076 - 0.178	Plastic Group II	80	Yes	Yes	-
	0.076 - 0.178	Plastic Group V	80	Yes	Yes	-
	0.076 - 0.178	Plastic Group VI	80	Yes	Yes	-
	0.076 - 0.178	Porcelain	60	Yes	Yes	-
	0.076 - 0.178	Plastic Group III	40	Yes	Yes	-

Report Date: 1994-07-28

Last Revised: 2018-07-02

© 2024 UL Solutions



