

Guide Information

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV, 3M CENTER, BLDG 230-3G-07, SAINT PAUL MN 55144-1001

9495LE, 9474LE

Pressure-sensitive laminating adhesives "3M® Laminating Adhesive"

Face Stock	Face Stock Thk mm	Application Surface	Max Temp (°C)	Min Temp (°C)	Indoor Use	Outdoor Use	Additional Conditions
Aluminum	0.051 - 0.813	Acrylic powder paint (smooth)	125	-40	Yes	No	-
	0.051 - 0.813	Alkyd paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Aluminum	125	-40	Yes	Yes	-
	0.051 - 0.813	Epoxy powder paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Galvanized steel	125	-40	Yes	Yes	-
	0.051 - 0.813	Polyester powder paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Polyurethane powder paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Porcelain	125	-40	Yes	No	-
	0.051 - 0.813	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.051 - 0.813	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
	0.051 - 0.813	Polypropylene	80	-40	Yes	Yes	-
	0.051 - 0.813	Acrylonitrile butadiene styrene	60	-40	Yes	Yes	-
	0.051 - 0.813	High density polyethylene	60	-40	Yes	No	-
	0.051 - 0.813	Polycarbonate	60	-40	Yes	Yes	-
	0.051 - 0.813	Low density polyethylene	40	-40	Yes	Yes	-
	0.051 - 0.813	Polystyrene	40	-40	Yes	Yes	-

Report Date: 1999-01-04
Last Revised: 2015-06-05

© 2024 UL Solutions

