

Model 4110, 5952, 5952P, 5952WF

File Number: MH17478

COMPANY

3M COMPANY
INDUSTRIAL ADHESIVES & TAPES DIV
3M CENTER
BLDG 230-3G-07
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

4110, 5952, 5952P, 5952WF

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Acrylic		-35	90	Yes	Yes	
Acrylic/Polyurethane paint		-35	90	Yes	Yes	
Aluminum		-35	90	Yes	Yes	
Coated Polycarbonate		-35	90	Yes	Yes	Polycarbonate coating limited to 3M Tape Primer 94 or 3M Adhesion Promoter 4298UV.
Enameled steel		-35	90	Yes	Yes	
Epoxy paint		-35	90	Yes	Yes	
Epoxy/Polyester paint		-35	90	Yes	Yes	
Galvanized steel		-35	90	Yes	Yes	
Glass epoxy		-35	90	Yes	Yes	
Nylon - Polyamide		-35	90	Yes	Yes	
Polybutylene terephthalate		-35	90	Yes	Yes	
Polycarbonate		-35	90	Yes	Yes	
Polyester paint		-35	90	Yes	Yes	

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Polyimide		-35	90	Yes	Yes	
Polyphenylene ether		-35	90	Yes	Yes	
Silane coated glass		-35	90	Yes	Yes	
Stainless steel		-35	90	Yes	Yes	
Uncoated glass		-35	90	Yes	Yes	
Polyethylene terephthalate (PET)		-35	85	Yes	Yes	
Acrylonitrile butadiene styrene		-35	75	Yes	Yes	
Rigid polyvinyl chloride		-35	75	Yes	Yes	
Cellulose acetate butyrate		-35	90	Yes	Yes	

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."