

# Model 4063, 4080, 5915, 5915P, 5915WF, 5925, 5925P, 5925WF, 5930, 5930P, 5930WF

File Number: MH17478

## COMPANY

### 3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV  
3M CENTER  
BLDG 230-3G-07  
SAINT PAUL, MN 55144-1001 United States

## MODEL INFO

4063, 4080, 5915, 5915P, 5915WF, 5925, 5925P, 5925WF, 5930, 5930P, 5930WF

| RATINGS                    |            |             |             |            |             |  |
|----------------------------|------------|-------------|-------------|------------|-------------|--|
| Surface                    | to Surface | Min Temp(C) | Max Temp(C) | Indoor Use | Outdoor Use | Surface Comment  |
| Acrylic/Polyurethane paint |            | -35         | 90          | Yes        | Yes         |  |
| Aluminum                   |            | -35         | 90          | Yes        | Yes         |  |
| Coated Polycarbonate       |            | -35         | 90          | Yes        | Yes         | Polycarbonate coating limited to 3M Tape Primer 94 or 3M Adhesion Promoter 4298UV. |
| Enameled steel             |            | -35         | 90          | Yes        | Yes         |  |
| Epoxy paint                |            | -35         | 90          | Yes        | Yes         |  |
| Epoxy/Polyester paint      |            | -35         | 90          | Yes        | Yes         |  |
| Galvanized steel           |            | -35         | 90          | Yes        | Yes         |  |
| Glass epoxy                |            | -35         | 90          | Yes        | Yes         |  |
| Nylon - Polyamide          |            | -35         | 90          | Yes        | Yes         |  |
| Polybutylene terephthalate |            | -35         | 90          | Yes        | Yes         |  |
| Polycarbonate              |            | -35         | 90          | Yes        | Yes         |  |
| Polyester paint            |            | -35         | 90          | Yes        | Yes         |  |
| Polyimide                  |            | -35         | 90          | Yes        | Yes         |  |

**RATINGS**

| <b>Surface</b>                   | <b>to Surface</b> | <b>Min Temp(C)</b> | <b>Max Temp(C)</b> | <b>Indoor Use</b> | <b>Outdoor Use</b> | <b>Surface Comment</b> |
|----------------------------------|-------------------|--------------------|--------------------|-------------------|--------------------|------------------------|
| Polyphenylene ether              |                   | -35                | 90                 | Yes               | Yes                |                        |
| Silane coated glass              |                   | -35                | 90                 | Yes               | Yes                |                        |
| Stainless steel                  |                   | -35                | 90                 | Yes               | Yes                |                        |
| Uncoated glass                   |                   | -35                | 90                 | Yes               | Yes                |                        |
| Polyethylene terephthalate (PET) |                   | -35                | 85                 | Yes               | Yes                |                        |
| Acrylonitrile butadiene styrene  |                   | -35                | 75                 | Yes               | Yes                |                        |
| Rigid polyvinyl chloride         |                   | -35                | 75                 | Yes               | Yes                |                        |
| Acrylic                          |                   | -35                | 90                 | Yes               | Yes                |                        |

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."