

Model 4912 (b), 4912F (b), 4955 (b), 4955F (b), 4959 (b), 4959F (b)

File Number: MH17478

COMPANY

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV  
3M CENTER  
BLDG 230-3G-07  
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

4912 (b), 4912F (b), 4955 (b), 4955F (b), 4959 (b), 4959F (b) where (b) - Substrates can be used with or without primer(s)/Coating. 3M Silane Coating, 3M Adhesion Promoter 4298UV and 3M Tape Primer 94 are used with glass substrate. 3M Primer AP111, 3M Adhesion Promoter 4298UV and 3M Tape Primer 94 are used with aluminum and galvanized steel substrates.

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Aluminum		-35	120	Yes	Yes	
Galvanized steel		-35	120	Yes	Yes	
Glass		-35	120	Yes	Yes	



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."