

Model 4914, 4920, 4930, 4950

File Number: MH17478

COMPANY

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV
3M CENTER
BLDG 230-3G-07
SAINT PAUL, MN 55144-1001 United States

MODEL INFO

4914, 4920, 4930, 4950

RATINGS						
Surface	to Surface	Min Temp(C)	Max Temp(C)	Indoor Use	Outdoor Use	Surface Comment
Aluminum		-35	110	Yes	Yes	
Ceramic		-35	110	Yes	Yes	
Enameled steel		-35	110	Yes	Yes	
Epoxy Glass Laminate (FR-4, G-10)		-35	110	Yes	Yes	
Galvanized steel		-35	110	Yes	Yes	
Stainless steel		-35	110	Yes	Yes	
Polybutylene terephthalate		-35	90	Yes	Yes	
Acrylonitrile butadiene styrene		-35	75	Yes	Yes	
Polycarbonate		-35	75	Yes	Yes	
Rigid Polyvinyl chloride		-35	75	Yes	Yes	



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."