

Model 4920, 4930, 4950

File Number: E464624

COMPANY

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV
 3M CENTER
 BLDG 230-3G-07
 SAINT PAUL, MN 55144-1001 United States

MODEL INFO

4920, 4930, 4950

SIGN ACCESSORIES	VALUE
Application	General Use Non-Electrical
Environmental Suitability	Wet, Damp or Dry Location

GENERAL			
Surface	Static Strength (psi)	Dynamic Bond Strength (psi)	Max Adhesive Temp (°C)
Acrylonitrile butadiene styrene	--	10	75
Polycarbonate	--	10	75
Aluminum	--	10	110
Galvanized steel	--	10	110
Enameled steel	--	10	110
Stainless steel	--	10	110
Rigid polyvinyl chloride	--	10	75
Glass/Epoxy (Grade G-10, FR-4)	--	10	110
Ceramic	--	10	110
Polybutylene Terephthalate	--	10	90
Acrylic	--	10	90

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL Solutions' Follow - Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL Solutions' Follow - Up Service. Always look for the Mark on the product.

UL Solutions permits the reproduction of the material contained in Product iQ subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from Product iQ with permission from UL Solutions" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "©2024 UL LLC."