

iq.ul.com

Marking and Labeling System Materials

MH26206

Guide Information

3M COMPANY

INDUSTRIAL ADHESIVES & TAPES DIV, 3M CENTER, BLDG 230-3G-07, SAINT PAUL MN 55144-1001

467MP, 467MPF, 467MPL, 467MPR, 468MP, 468MPF, 468MPL, 468MPR, 7952MP, 7952MPL, 7955MP, 7955MPL, 7962MP, 7962MPL, 7965MP, 7965MPL, 9172MP, 918MP, 9185MP, 9188MP, 9437MP, 9667MP, 9676MP, 9668MP, 9668MPL, CDB610

Pressure-sensitive laminating adhesives "3M® Laminating Adhesive"

<u>Face Stock</u>	<u>Face Stock</u> <u>Thk mm</u>	<u>Application Surface</u>	<u>Max Temp</u> <u>(°C)</u>	<u>Min Temp</u> <u>(°C)</u>	<u>Indoor</u> <u>Use</u>	<u>Outdoor</u> <u>Use</u>	<u>Additional</u> <u>Conditions</u>
Aluminum	0.051 - 0.813	Aluminum	150	-40	Yes	Yes	-
	0.051 - 0.813	Galvanized steel	150	-40	Yes	Yes	-
	0.051 - 0.813	Porcelain	150	-40	Yes	Yes	-
	0.051 - 0.813	Stainless steel	150	-40	Yes	Yes	-
	0.051 - 0.813	Alkyd paint	125	-40	Yes	Yes	-
	0.051 - 0.813	Polyester paint	100	-40	Yes	Yes	-
	0.051 - 0.813	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.051 - 0.813	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.051 - 0.813	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
Polycarbonate	0.127 - 0.508	Epoxy	100	-40	Yes	Yes	-
	0.127 - 0.508	Polyester paint	100	-40	Yes	Yes	-
	0.127 - 0.508	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.127 - 0.508	Alkyd paint	80	-40	Yes	Yes	-
	0.127 - 0.508	Aluminum	80	-40	Yes	Yes	-
	0.127 - 0.508	Galvanized steel	80	-40	Yes	Yes	-
	0.127 - 0.508	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.127 - 0.508	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
	0.127 - 0.508	Polycarbonate	60	-40	Yes	Yes	-
	0.127 - 0.508	Polyurethane paint	60	-40	Yes	Yes	-
	0.127 - 0.508	Porcelain	60	-40	Yes	Yes	-
	0.127 - 0.508	Stainless steel	60	-40	Yes	No	-
Polyester	0.076 - 0.178	Polyester paint	100	-40	Yes	Yes	-
	0.076 - 0.178	Acrylonitrile butadiene styrene	80	-40	Yes	Yes	-
	0.076 - 0.178	Alkyd paint	80	-40	Yes	Yes	-
	0.076 - 0.178	Aluminum	80	-40	Yes	Yes	-
	0.076 - 0.178	Epoxy	80	-40	Yes	Yes	-
	0.076 - 0.178	Galvanized steel	80	-40	Yes	Yes	-
	0.076 - 0.178	Nylon - Polyamide	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyethylene terephthalate	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyphenylene oxide/ether	80	-40	Yes	Yes	-
	0.076 - 0.178	Polyurethane paint	60	-40	Yes	Yes	-
	0.076 - 0.178	Porcelain	60	-40	Yes	Yes	-
	0.076 - 0.178	Stainless steel	60	-40	Yes	No	-
0.076 - 0.178	Polycarbonate	40	-40	Yes	Yes	-	

<u>Canadian Application</u> <u>Face Stock</u>	<u>Face Stock</u> <u>Thk mm(in)</u>	<u>Canadian Application Surface</u>	<u>Max Temp</u> <u>(°C)</u>	<u>Indoor</u> <u>Use</u>	<u>Outdoor</u> <u>Use</u>	<u>Additional</u> <u>Conditions</u>
Aluminum	0.051 - 0.813	Metals	150	Yes	Yes	-
	0.051 - 0.813	Porcelain	150	Yes	Yes	-
	0.051 - 0.813	Plastic Group II	80	Yes	Yes	-
	0.051 - 0.813	Plastic Group V	80	Yes	Yes	-
	0.051 - 0.813	Plastic Group VI	80	Yes	Yes	-
Polycarbonate	0.127 - 0.508	Metals	100	Yes	Yes	-
	0.127 - 0.508	Plastic Group VIII	100	Yes	Yes	-
	0.127 - 0.508	Plastic Group II	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group V	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group VI	80	Yes	Yes	-
	0.127 - 0.508	Plastic Group III	60	Yes	Yes	-
Polyester	0.076 - 0.178	Metals	100	Yes	Yes	-
	0.076 - 0.178	Plastic Group II	80	Yes	Yes	-
	0.076 - 0.178	Plastic Group V	80	Yes	Yes	-
	0.076 - 0.178	Plastic Group VI	80	Yes	Yes	-
	0.076 - 0.178	Plastic Group VIII	80	Yes	Yes	-
	0.076 - 0.178	Porcelain	60	Yes	No	-

Report Date: 1987-06-18

Last Revised: 2013-04-04

© 2024 UL Solutions

